



PAT3319DP

Key Features:

- 2x19 dBi Directional Gain
- Dual Polarization H&V in One Case
- Outdoor Weatherproof Enclosure
- High Quality Construction
- Heavy-Duty Mounting Elements
- Easy Elevation and Tilt Adjustment
- 5 Years Warranty
- Designed for All Weather Operation



Applications:

- 3.5 GHz Band Wireless LAN
- WLAN Systems
- MIMO

Description:

Antenna working in 3.5 GHz band with two independent directional panel antennas with 2x19 dBi gain with vertical and horizontal polarization. It is the ideal solution for MIMO and Nstreme dual configuration. Perfectly designed for operation under severe weather conditions. Proper materials allow operation in the salty water environment without corrosion. High quality construction of pole mounting elements guarantee easy elevation and easy tilt down as well as rock-stable operation. It can be used as customer premise equipment and also as small base stations.

Electrical Properties	
Frequency	3.3 - 3.5 GHz
Gain	2x19dBi
Polarization	dual H&V
Beamwidth deg horizontal	20°
Beamwidth deg vertical	20°
VSWR	<1.8
Impedance	50 ohm
Front to back ratio	> 35 dB
Enclosure Properties	
Technology:	Microstrip
Material:	UV protected
Colour:	White
Min temperature:	-40°C / -40°F
Max temperature:	80°C / 176°F
Mechanical Properties	
Input Connector	N-type / female
Outside Dimensions	345x345x20mm / 13.6x13.6x0.8"
Weight	1.3kg / 2,9lbs

Specification subject to change without notice.